



Recessed LED spotlight

Materials:

metal alloy, thermoplastic polymers

Finishes:

gold plated, chrome plated, antique bronze, antique pewter, antique gold, brown, oriental silver

Light source:

SMD LED module

Wiring:

2000mm

Application type:

inside cabinet, under cabinet, under shelf

Installation:


recessed


Patented














Colour appearance natural white 4300 K **Colour temperature** 390 lm Luminous flux 130 lm/W Luminous efficiency

> Ra ≥ 80 CRI

Colour appearance warm white **Colour temperature** 3000 K 360 lm **Luminous flux** Luminous efficiency 120 lm/W

> CRI Ra ≥ 80

Colour appearance super warm white


2700 K **Colour temperature** 360 lm Luminous flux Luminous efficiency 120 lm/W Ra ≥ 80

CRI

52









installation on wood panels

Code	Watt & Volt	Light colour
12590N	3W @ 12Vdc	natural white
12590B	3W @ 12Vdc	warm white
12590B1	3W @ 12Vdc	super warm white

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.







SETS OF 2, 3, 4 OR 5 AKOYA 2.0 AND LED CONVERTER ARE AVAILABLE ON REQUEST.

Code	Finish
80	gold plated
09	chrome plated
18	antique bronze
29	antique pewter
38	antique gold
39	brown
40	oriental silver



For Tunable White and White Changeable versions, consult the Tunable White & White Changeable collection catalogue also available on www.domusline.com.





N This drawing shows the spotlight's overall dimensions. See installation manual for more details.

Recessed installation on wood panels with 68mm hole, using a functional fixing system with side-pressed steel springs.











¹ For UL-certified model codes, see the American standard LED collection catalogue, also available at www.domusline.com





53

FINISHES



GOLD PLATED (code 08)



ANTIQUE GOLD (code 38)



CHROME PLATED (code 09)



BROWN (code 39)



ANTIQUE BRONZE (code 18)



ORIENTAL SILVER (code 40)



ANTIQUE PEWTER (code 29)

www.domusline.com