





FLEXYLED HE CR

Domus Line design

Flexible LED modules for back-to-back connection

Materials:

flexible LED strip with adhesive

Covering:

highly transparent resin

Light source:

static light LED module

Number of LEDs:

120 LED/metre

Application type:


universal

Installation:

surface or integrated in the profiles


FLEXYLED HE CR is an LED strip with **a static light source having 120 LED/metre** with high linear luminosity which avoid the spot effect. Developed with an innovative **rapid connection** system which allows you to connect modules of various lengths back-to-back. These modules **(50 cm, 100 cm, 200 cm & 300 cm)** are all divisible **every 5 cm**.





Colour appearancenatural whiteColour temperature4500 KelvinLuminous efficiency85 Im/WCRIRa ≥ 80





TECHNICAL DATA

 Power supply
 24Vdc

 LEDs/metre
 120

Divisibility
Protection



54 www.domusline.com

^{*} values refer to FLEXYLED HE CR 1000 mm







FLEXYLED HE CR

modules with 120 LED/m



Code	Length	Watt & Volt	Light colour	LED
1207301N/50	500 mm	4.8W @ 24Vdc	natural white	60
1207301N/100	1000 mm	9.6W @ 24Vdc	natural white	120
1207301N/200	2000 mm	19.2W @ 24Vdc	natural white	240
1207301N/300	3000 mm	28.8W @ 24Vdc	natural white	360

Code	Length	Watt & Volt	Light colour	LED
1207301B/50	500 mm	4.8W @ 24Vdc	warm white	60
1207301B/100	1000 mm	9.6W @ 24Vdc	warm white	120
1207301B/200	2000 mm	19.2W @ 24Vdc	warm white	240
1207301B/300	3000 mm	28.8W @ 24Vdc	warm white	360

LED CONVERTER AND POWER CABLE NOT INCLUDED. TO BE ORDERED SEPARATELY.



FLEXYLED HE CR

angled modules






Code	Length	Watt & Volt	Light colour	Model
1207701N	60x60 mm	1.1W @ 24Vdc	natural white	left
1207701B	60x60 mm	1.1W @ 24Vdc	warm white	left

Code	Length	Watt & Volt	Light colour	Model
1207601N	60x60 mm	1.1W @ 24Vdc	natural white	right
1207601B	60x60 mm	1.1W @ 24Vdc	warm white	right





9

Cables

for FLEXYLED HE CR

Ref.	Code	Length	Model
А	1149501	2000 mm	power cable
В	1149601/5	50 mm	connection cable
В	1149601/50	500 mm	connection cable



The 2-metre power cable and connection cables ensure electrical continuity and are supplied with multipolar connectors.

В



Α





FOR LED CONVERTERS AND ACCESSORIES SEE PAGE 68.

¹ For codes for UL-certified models, consult the catalogue for the American standard LED collection also available at www.domusline.com.