



## **Recessed LED spotlight**

#### Materials:

metal alloy, thermoplastic polymers

## Finishes:

gold plated, chrome plated, antique pewter, antique gold, brown

#### Light source:

SMD LED module

#### Wiring:

2000mm

### **Application type:**


inside cabinet, under cabinet, under shelf

#### Installation:

recessed


**Patented** 





50






Lux

1250

350



Colour appearance natural white 4300 K **Colour temperature** 390 lm Luminous flux 130 lm/W Luminous efficiency

**CRI** Ra ≥ 80

warm white **Colour appearance Colour temperature** 3000 K 360 lm **Luminous flux** Luminous efficiency 120 lm/W CRI Ra ≥ 80


**Colour appearance** super warm white

2700 K **Colour temperature** 360 lm Luminous flux Luminous efficiency 120 lm/W **CRI** Ra ≥ 80

50







# 

Code	Watt & Volt	Light colour
12541N	3W @ 12Vdc	natural white
12541B	3W @ 12Vdc	warm white
12541B1	3W @ 12Vdc	super warm white

#### LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.







SETS OF 2, 3, 4 OR 5 HYPNOSE 2.0 AND LED CONVERTER ARE AVAILABLE ON REQUEST.

Code

80

09

29

38

39

Finish

gold plated

chrome plated

antique pewter

antique gold

brown

N This drawing shows the spotlight's overall dimensions. See installation manual for more details.

Recessed installation on wood panels with 68mm hole, using a functional fixing system with side-pressed steel springs.





For Tunable White and White Changeable versions, consult the Tunable White & White Changeable collection catalogue also available on www.domusline.com.





## **FINISHES**



GOLD PLATED (code 08)



ANTIQUE GOLD (code 38)



CHROME PLATED (code 09)



BROWN (code 39)



ANTIQUE PEWTER (code 29)







<sup>1</sup> For UL-certified model codes, see the American standard LED collection catalogue, also available at www.domusline.com





51

www.domusline.com