



Recessed LED spotlight

Materials:

metal alloy, thermoplastic polymers

Finishes:

gold plated, chrome plated, antique bronze, antique pewter, antique gold, brown

Light source:

SMD LED module

Wiring:

2000mm

Application type:

inside cabinet, under cabinet, under shelf

Installation:


recessed


Patented














Colour appearance natural white Colour temperature 4300 K Luminous flux 390 lm

Luminous efficiency 130 lm/WCRI Ra ≥ 80

Colour appearance warm white
Colour temperature 3000 K

Luminous flux 360 lm
Luminous efficiency 120 lm/W

CRI Ra ≥ 80

Colour appearance super warm white

 Colour temperature
 2700 K


 Luminous flux
 360 lm

 Luminous efficiency
 120 lm/W

CRI Ra ≥ 80







Ø78







Light colour

natural white

warm white

super warm white





Code Finish 08 gold plated 09 chrome plated 18 antique bronze 29 antique pewter

gold plated

brown

38

39

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.

Watt & Volt

3W @ 12Vdc

3W @ 12Vdc

3W @ 12Vdc



12592_ _N

12592__B

12592__B1





SETS OF 2, 3, 4 OR 5 PASSEPARTOUT 2.0 AND LED CONVERTER ARE AVAILABLE ON REQUEST.



For Tunable White and White Changeable versions, consult the Tunable White & White Changeable collection catalogue also available on www.domusline.com.

For LED converters and accessories see page 74 or consult the DomusExtra catalogue also available on









Recessed installation on wood panels with 68mm hole, using a functional fixing system with side-pressed steel springs.





¹ For UL-certified model codes, see the American standard LED collection catalogue, also available at www.domusline.com





57

FINISHES



GOLD PLATED (code 08)



ANTIQUE GOLD (code 38)



CHROME PLATED (code 09)



BROWN (code 39)



ANTIQUE BRONZE (code 18)



ANTIQUE PEWTER (code 29)

www.domusline.com